

Thank you for purchasing the Craven Speed Fiat Wiper Delete Kit

Contents:




- 1 Aluminum Cap
- 1 Grommet
- 1 6mm Bolt
- 1 Square O-ring
- 1 Washer
- 1 6mm Lock Nut
- 1 Wiper Tube Plug

Tools Required:

- Phillips Screwdriver
- Torx driver
- Socket Wrench
- 13mm Socket
- 10mm Socket
- Scissors
- 4.5mm Allen Key



Read all Directions Carefully Before Proceeding

1. Using a 10mm socket, remove the nut securing the wiper blade and then the blade itself.
2. Open the back hatch. Using the plastic prybar, remove the 8 panel rivets from the paneling.
3. Unscrew the hatch cord with a 5mm Hex driver. The paneling will still be connected by clips at the top, but you will now have access to the wiper motor.
4. Disconnect the cords connected to the wiper motor by pressing down on the plastic tab, and pulling gently.
5. Remove the three bolts securing the wiper motor with the 10mm socket. Be careful to support the motor with a free hand. Once the three bolts are removed, the wiper motor can be taken out of the car.
6. Remove the existing rubber grommet from the hole in the glass. Just pull. Clean the surrounding glass. Replace the OEM grommet with the supplied grommet.
7. Place wiper delete cap onto the grommet. Place the included square o-ring over the 6mm bolt and insert into the center of the wiper delete cap.
8. Open the rear hatch door. While holding the 6mm bolt in place with a 4.5mm allen key, place the large washer over the bolt on the under side of the hatch door and attach the lock nut. Tighten until the 6mm bolt is sitting approx. 1mm below flush.
9. Replace the panel rivets and the hatch cord.

Questions, Comments, Suggestions?
Call CravenSpeed at 503-505-6886
or Email: support@cravenspeed.com